

## LHM100UL

Specifications					LHM100UL	LHM100UL	LHM100UL	LHM100UL
Identification	1.1	Manufacturer			Toyota	Toyota	Toyota	Toyota
	1.2	Manufacturer's type designation			LHM100UL	LHM100UL	LHM100UL	LHM100UL
	1.4	Operator type			Hand	Hand	Hand	Hand
	1.5	Load capacity/rated load	Q(t)	kg	1000	1000	1000	1000
	1.6	Load centre distance	c	mm	300	400	600	1000
	1.8	Load distance, centre of drive axle to fork	x	mm	330 <sup>1)</sup>	530 <sup>1)</sup>	880 <sup>1)</sup>	1730 <sup>1)</sup>
	1.9	Wheelbase	y	mm	580 <sup>1)</sup>	780 <sup>1)</sup>	1130 <sup>1)</sup>	1980 <sup>1)</sup>
Weight	2.1	Service weight		kg	58	64	80	125
Wheels	3.1	Steer/fork wheels: Steel (S), Nylon (N), Polyurethane (P)			N/P, S	N/P, S	N/P, S	N/P, S
	3.2	Wheel size, front			175x60	175x60	175x60	175x60
	3.3	Wheel size, rear			—/38x76 <sup>2)</sup>	—/38x76 <sup>2)</sup>	—/38x76 <sup>2)</sup>	—/38x76 <sup>2)</sup>
	3.5	Wheels, number front/rear (x = driven wheels)			2/4	2/4	2/4	2/4
	3.6	Track width, front	b <sub>10</sub>	mm	132	132	132	132
	3.7	Track width, rear	b <sub>11</sub>	mm	364	364	364	364
Dimensions	4.4	Lift	h <sub>3</sub>	mm	100	100	100	100
		Lift height	h <sub>23</sub>	mm	138	138	138	138
	4.9	Height of tiller in drive position, min./max.	h <sub>14</sub>	mm	1220	1220	1220	1220
	4.15	Height, lowered	h <sub>13</sub>	mm	38	38	38	38
	4.19	Overall length	l <sub>1</sub>	mm	970	1170	1520	2370
	4.20	Length to face of forks	l <sub>2</sub>	mm	370	370	370	370
	4.21	Overall width	b <sub>1</sub> /b <sub>2</sub>	mm	520	520	520	685
	4.22	Fork dimensions	s/e/l	mm	38/156/600	38/156/800	38/156/1150	38/156/2000
	4.25	Width over forks	b <sub>5</sub>	mm	520	520	520	520
	4.32	Ground clearance, centre of wheelbase	m <sub>2</sub>	mm	5	5	5	5
	4.33	Aisle width for pallets 1000x1200 crossways	A <sub>st</sub>	mm	—	—	1595 <sup>1)</sup>	—
	4.34	Aisle width for pallets 800x1200 lengthways	A <sub>st</sub>	mm	—	—	1795 <sup>1)</sup>	—
	4.35	Turning radius	W <sub>a</sub>	mm	825 <sup>1)</sup>	1025 <sup>1)</sup>	1375 <sup>1)</sup>	2225 <sup>1)</sup>
Other		Support wheels			No	No	No	Yes/Nylon
		Outside width of steel arm for support wheels		mm	—	—	—	685
		Pump unit			Quicklift, overload			

1) Distance with forks raised.

2) Singel wheel/bogie wheel.

## Dimensional drawings

